

PA1022/POE1016 Series

Desk Top Type Type IEC320/C8

Features

Over-Voltage Protection
Over-Current Protection

Short-circuit Protection
100%Hi-pot & ATE(Chroma)Tested

100%Burn-in under High
Ambient Temperature(45°C)

Low Ripple/Noise
MTBF Above 50000 HRS At 25°C

LVD authentication
Limited Power Sources(LPS)

CEC IV and V Efficiency
Regulations Compliance

Cispr 22 CLASS B, VCCI CLASS B,
FCC Part15 CLASS B, Compliance



Specification

Model No Part No Item	PA1022-xT2Bz			POE1016-xT2Bz		
	PA1022-120T2B~ PA1022-150T2B	PA1022-151T2B~ PA1022-300T2B	PA1022-301T2B~ PA1022-570T2B	POE1016-120T2B~ POE1016-149T2B	POE1016-150T2B~ POE1016-300T2B	POE1016-301T2B~ POE1016-570T2B
Output Voltage	12~15V	15.1~30V	30.1~57V	12~14.9V	15~30V	30.1~57V
Output Current(Max.)	2.0A	1.6A	0.8A	1.25A	1.0A	0.49A
Output Power(Max.)	24W	24W	24W	15W	15W	15W
Input Voltage	AC90~264V			AC90~264V		
Input Frequency	47~63Hz			47~63Hz		
Input Current	0.6A Maximum			0.4A Maximum		
Inrush Current	40A Maximum			40A Maximum		
Line Regulation	1% Maximum			1% Maximum		
Ripple&Noise	1% Maximum			1% Maximum		
Load Regulation	5% Maximum			5% Maximum		
Efficiency	≥ 75%			≥ 75%		
Operating Temperature	0~40°C			0~40°C		
Storage Temperature	-20~85°C			-20~85°C		
Over-Voltage Protection	Auto Recovery			Auto Recovery		
Short-circuit Protection	Auto Recovery			Auto Recovery		
Safety Standard	CB			CB		
EMC(EMI/EMS)						

機種編碼 Products code:

