

Features

Over-Voltage Protection
Over-Current Protection

Limit current Protection(Optional)

Short-circuit Protection
100%Hi-pot & ATE(Chroma)Tested

100%Burn-in under High
Ambient Temperature(40°C)

Low Ripple/Noise
MTBF Above 50000 HRS At 25°C

LVD authentication
Limited Power Sources(LPS)

CEC IV and V Efficiency
Regulations Compliance

Cispr 22 CLASS B,VCCI CLASS B,
FCC Part15 CLASS B, Compliance

PA1005 Series

Wall Mount/Horizontal Type
For U.S.A



Specification

Model No Part No Item	PA1005-1HU		PA1005-2HU	
	PA1005-030HU~ PA1005-074HU		PA1005-075HU~ PA1005-150HU	
Output Voltage	3~4.9V	5.0~7.4V	7.5~12V	12~15V
Output Current(Max.)	1.5A	1A	0.67A	0.5A
Output Power(Max.)	5W	5W	5W	6W
Input Voltage	AC 90~264V			
Input Frequency	47~63Hz			
Input Current	0.2A Maximum			
Inrush Current	40A Maximum			
Line Regulation	1% Maximum			
Ripple& Noise	2% Maximum			
Load Regulation	5% Maximum			
Efficiency	64~71%			
Operating Temperature	0~40°C			
Storage Temperature	-20~85°C			
Over-Voltage Protection	Auto Recovery			
Short-circuit Protection	Auto Recovery			
Safety Standard	CB,MET,DOE,BSMI,Nrcan,GS			
EM C(EMI/EMS)	CE,FCC,VCCI,C-tick			

機種編碼 Products code:

